

Touch the future, light up life.



TD-D2ICR88-TY

2-Wire IP Video Intercom Kit ——










intercom



photo



video



monitor



IC card unlock



visitor record



pedestrian detection



infrared fill light









Tuya APP

cloud storage alarm message video playback

Product Features

- Large Screen Display: Features a 7-inch LCD screen with a resolution of 1024x600 IPS.
- Advanced Communication: Supports intercom, photo capture, video recording, remote unlocking, and visitor record
- Enhanced Features: Incorporates pedestrian detection, calendar display, and adjustment options for brightness, contrast, and color.
- Secure Lock Control: Offers compatibility with magnetic locks and electric locks, complete with locking delay time settings.
- Connectivity and App Integration: Connects through 2.4G WiFi and seamlessly integrates with the Tuya/Trudian APP.
- IC Card Unlocking: Provides the convenience of IC card unlocking.

Produce Size The Produce Size The Product of the Pr



Indoor Monitor

Outdoor Station

Adapter	Input: AC100-240V 50Hz/60Hz Output: DC12V 2A

Power Consumption Static State < 3.5W, (indoor+outdoor) Working State < 8W

Whole Unit

Distance between o~15m(RVV4*0.2mm²) outdoor station and indoor monitor

Unlocking Wiring 0~10m (RVV2*1.0mm²)

Current and Voltage <30 \ 3A of Gate Lock

Wiring 2-wire

Relative Humidity 10%~90% (RH)

Tuya APP20 users capacity, supports functions including: intercom, photo, video, monitor, unlock, cloud storage, alarm message, video playback.

Product Specifications

Indoor Monitor	
Dimensions	210x143x17.5mm
Screen Size	7 inches LCD
Screen Resolution	1024*600 IPS
Power Consumption	working state <8W, static <3.5W
Sound	70-80 dB (<30cm)
Working Temperature	-10°C ~ 50° C
Network	2.4G WIFI
Functions	intercom, photo, video, unlock, visitor record, pedestrian detection, calendar display, adjust brightness & contrast & color, lock delay adjustment, multi-language OSD menu
Expanded Memory	external TF card to automatically save photo

video and message

O. . + - | - - . . C + - . + : - . -

Outdoor Station		
Dimensions	66x138x23.5mm	
Pixel	2 million pixels/1080P (AHD signal)	
View Angle	140 degrees horizontal angle	
Night Vision	IR CUT switch, high color precision, black and white image	
Fill Light	940nm(Infrared)	
Lock Control	Connectable to magnetic lock and electric lock, indoor unit has locking delay time setting	
IC Card Unlock	yes	
Power Consumption	Working state< 5W, Static <1W	
Sound	60-70dB (<30cm)	

-20°C~50°C

IPx4

Wiring Diagram

Product

Specifications

2-wire Connection Uninterrupted Power Supply NO NC GND +12V PUSH +CONTROL-LINE1+ LINE1- LINE2+ LINE2- BELL LINE1+ LINE1- LINE2+ LINE2- BELL DCIN- DCIN+ GND DCIN- DCIN+ GND GND DOOR NC COM NO 2 Wires 2 Wires

Packing List





Operating Temperature

IP Rating









Outdoor Station Indoor Monitor

Bracket for indoor unit

Adapter

Screws & anchors

IC cards



Website: www.trudian.com/en/

Address: Farbell Technology Park, Yixian Road, Nanlang, Cuiheng New District, Zhongshan City, Guangdong Province,

China.Zip Code:528451 Phone: +86-0760-23689666 E-mail: sales@trudian.net



